

BOSTIK 9907 SOLVENT

PRODUCT

Bostik 9907 is a blended solvent mixture.

DESCRIPTION

Bostik 9907 is a colourless cleaner/primer used for preparing various surfaces prior to bonding with polyurethane on nitrile based adhesives.

RECOMMENDED USES

- As a general purpose cleaner
- As a thinner for PU and nitrile based adhesives.
- As an effective substrate cleaner where polyurethane sealants are to be used.
- For cleaning up adhesive spills

FEATURES & BENEFITS

- Effective and quick acting
- Simple to use

PERFORMANCE PROPERTIES

Type	Solvent Blend
Colour	Colourless
Flash point	< 0°C
S.G.	0.82

PACKAGING

Available in 4lt and 20lt containers

APPLICATION INSTRUCTIONS

- Use with clean rag on stiff brush
- When using as thinning agent do not dilute adhesives more than 5%

PRECAUTION

- Highly flammable
- Keep covered when not in use due to high volatility (evaporates quickly).

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

On contact, uncured solvent causes irritation. Gloves and protective goggles must be worn during application and use.

- Avoid contact with skin, eyes and avoid breathing in vapour.
- Wear protective gloves when mixing or using
- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed, do not induce vomiting. Give a glass of water.
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.
- For more detailed information refer to Material Safety Data Sheet.

STORAGE/SHELF LIFE

- Store in well ventilated area
- Keep under cover between 5°C to 25°C
- Store away from all heat sources.

Shelf Life is a minimum of 5 years if stored as above

FIRE

Highly Flammable

BOSTIK 9907 SOLVENT

ITEM NO.	STOCK SIZE
045292	Bostik 9907 4lt
045306	Bostik 9907 20lt

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD



BOSTIK
AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

BOSTIK
NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

FOR FURTHER INFORMATION

BOSTIK
SINGAPORE PTE LTD
Phone: +65-6863 4088
Fax: +65-6863 4077

PERTH
Phone: 08 9331 7666
Fax: 08 9331 7677

BRISBANE
Phone: 07 3260 2206
Fax: 07 3260 2123

BOSTIK
(MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

Product:	Bostik 9907
Issue Date:	February 2002
Issue No:	1
Division:	Industrial
Total Pages:	1

(ABN 79 003 893 838)