

*you can **RELY** on*

**CEMENTAID**

*The Way to Better Concrete*

## Waterproofing and Admixtures

# EVERDURE CALTITE

*For Prevention of Disintegration of Concrete through attack by Sulphate/Chloride Soluable Salts,  
and also specialised construction applications.*

### SHORT SPECIFICATION

All concrete (specify areas) to be constructed in accordance with the drawings, and strictly in accordance with current, detailed, Cementaid Everdure Caltite System specifications, using not less than 350kg of Ordinary Portland Cement per cubic metre, and having a W/C Ratio not in excess of 0.42, and achieving a water absorption rating of not more than 1% (one percent) w/w of concrete, when tested in accordance with BSS 1881 part 122, 1983, except that the age at test shall be 7 days, in conjunction with structural reinforcement of hard rib deformed bars and top steel reinforcement grid and other details conforming to current recommendations and requirements of Cementaid.

*For full Detailed Specifications, [click here](#)*

INDUSTRIAL FLOOR SPECIFICATIONS - GEL CONTROL AGENT - ANTI-CORROSION  
IMPREGNATIONS - OIL & SOLVENT PROOFING - WATERPROOFING - RAPID HARDENING  
RETARDING - SURFACE TOUGHENING - MORTAR AND DAMPCOURSE ADMIXTURES, ETC.

*The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.*

[Contact Cementaid](#)

[Product Range](#)

[Home Page](#)

[Locations](#)

**SPEC-NET**

Building & Construction