

*you can **RELY** on*

CEMENTAID

The Way to Better Concrete

Form Oils, Curing & Bonding Agents

CALCURE HR

High Efficiency Concrete Curing - Single spray application, without covering or continuous water spray/ponding

EFFECTS:

Calcure HR is a special formulation, incorporating hydrocarbon resin blends, which seals the surface of fresh concrete, reducing moisture loss and providing high efficiency curing. Calcure HR complies with AS 3799 and RTA 3202.

**WHERE
RECOMMENDED:**

All concrete surfaces which will be subjected to traffic during the curing period, and areas to which standard curing methods would be difficult or uneconomical. After the curing period, preferably at the end of the job, an application of CEMENTAID ROKITE will seal the dry concrete against dusting, oil and grease and facilitate cleaning.

CONTACT CEMENTAID FOR APPLICATION SERVICE

CAUTION:

Do not specify Calcure HR or any other curing compounds where liquid surface hardeners such as CEMENTAID DIAMITE are specified to be used, as penetration of these treatments would be impaired. In such cases, specify water, damp sand or building plastic.

For application, "Rega" or equivalent pneumatic knapsack spray is recommended with No. 9, 10 or 11 fantail nozzles. Equipment should be cleaned with white spirit or similar solvents.

SPECIFICATIONS

All concrete shall be cured by a liberal application of Cementaid Calcure HR sprayed on to the surface as soon as possible after finishing or removal of forms, at a rate of 5-7 square metres per litre.

**INDUSTRIAL FLOOR SPECIFICATIONS - GEL CONTROL AGENT - ANTI-CORROSION
IMPREGNATIONS - OIL & SOLVENT PROOFING - WATERPROOFING - RAPID HARDENING
RETARDING - SURFACE TOUGHENING - MORTAR AND DAMPCOURSE ADMIXTURES, ETC.**

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such

use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

[Contact Cementaid](#)

[Product Range](#)

[Home Page](#)

[Locations](#)

