

*you can **RELY** on*

**CEMENTAID**

*The Way to Better Concrete*

## Wall Surface Treatments

### **DRIWAL P6**

**Long term protection and preservation of concrete, brick and stonework against weathering, staining or mould decay, without affecting natural texture or appearance. Long term preservation of breathing type exterior paints and asbestos cement sheets in near new condition.**

#### **EFFECTS:**

Cementaid **DRIWAL P6** is a unique calcium reactive, long-life silicone masonry preserver and impregnation, which keeps concrete, brick and stonework looking clean and new. The specially modified silicone chains of **DRIWAL P6** chemically bond with calcareous materials in the outer 5mm of surface masonry, and become part of the surface. This greatly extends the effective life of **DRIWAL P6** over ordinary silicone treatments. **DRIWAL P6** leaves no visible surface film, and so preserves the completely natural appearance of surfaces. The surface can 'breathe' but is water repellent in depth and sterilised against mould, fungus and organic growth staining, as well as preventing leaching and staining by efflorescence. Effective life 7 to 10 years. Typical test - Units of moisture passing per hour, after 100 hours - **DRIWAL P6** 0.15 (typical figure); untreated - 1.20.

#### **COVERAGE:**

Breathing type paints	Not less than 1 litre per 6.0m <sup>2</sup>
Pressed clay brickwork	Not less than 1 litre per 5.0m <sup>2</sup>
Texture and wire cut bricks	Not less than 1 litre per 3.5m <sup>2</sup>
Concrete and cement render	Not less than 1 litre per 4.0m <sup>2</sup>
Concrete block	Not less than 1 litre per 1.5m <sup>2</sup>

(Where very porous, specify **Cementaid SILICONE S50** in preference to **DRIWAL P6**, at same coverage rate)

Asbestos cement roofing and wall cladding

(Natural finish)	Not less than 1 litre per 3.3m <sup>2</sup>
Sandstone	Not less than 1 litre per 2.0m <sup>2</sup>
Mt. Gambier Stone	Not less than 1 litre per 1.5m <sup>2</sup>
W.A. Limestone	Not less than 1 litre per 1.5m <sup>2</sup>
Terracotta or cement tiles	Not less than 1 litre per 5.0m <sup>2</sup>

Check small test area first to ensure suitability of colour to **DRIWAL P6**.

## WHERE

### RECOMMENDED:

All external natural masonry, concrete, brick or rendered surfaces. Asbestos cement roofs and cladding. Exterior concrete surfaces. Primer for all paint work to extend paint life (exterior). Paint primer over 'green' cement where flushing urgent after rendering. For correction of damp walls and other special uses, consult **CEMENTAID** for many special uses.

### SPECIFICATIONS FOR CHOSEN AREAS:

All surfaces (specify areas) shall be protected against weathering, grime, mould and decay by a single saturation impregnation with calcium-reactive **DRIWAL P6** Specification Grade at the rate of not less than one litre per ... sq. m. (here specify area for type of surface to be treated from above table.)

NOTE: One application of **DRIWAL P6** only, is usually necessary, due to its unique reactive properties.

## SPECIFICATIONS

All exposed exterior surfaces of the building other than metal, wood and glass surfaces and surgaces protected by oil paints, when clean, dry and complete shall be protected against weathering, grime, mould and decay by a single saturating impregnation of **CEMENTAID** calcium reactive **DRIWAL P6**. The **DRIWAL P6** shall be flooded on from the top downwards with a minimum run down of 20cm by low pressure pump or spray at the minimum rates for various surfaces as stated.

INDUSTRIAL FLOOR SPECIFICATIONS - GEL CONTROL AGENT - ANTI-CORROSION IMPREGNATIONS - OIL & SOLVENT PROOFING - WATERPROOFING - RAPID HARDENING RETARDING - SURFACE TOUGHENING - MORTAR AND DAMPCOURSE ADMIXTURES, ETC.

*The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.*

[Contact Cementaid](#)

[Product Range](#)

[Home Page](#)

[Locations](#)

**SPEC-NET**