

*you can **RELY** on*

CEMENTAID

The Way to Better Concrete

Floor Surface Treatments

ROKITE

To seal and protect concrete floors against surface corrosion and staining from oils, grease, fats, sugars, lactic acids, mild acids or caustic solutions, solvents, lubricants, etc.

EFFECTS:

ROKITE is a corrosion & stain resistant impregnation and sealer for beautifying and protecting new or old concrete floors.

ROKITE is a unique blend of toughened plastic and rubber resins in a penetrating solvent, which can be coloured or clear, depending on requirements. **ROKITE** penetrates the concrete surface and seals pores to a depth of 3mm or more, binding up this layer with **ROKITE** resins, as well as leaving a tough, durable, hard wearing surface film. Grease, oil, food spillages etc. simply wipe or hose off. Dusting is completely eliminated, reducing cleaning time and costs. Attack by a wide range of corrosive or staining materials is resisted, and absorption of food materials that convert to acids by bacterial or enzyme action is greatly restricted. Concrete surface is physically hardened. Effective life - 2 to 3 times more than similar untreated surfaces. Improves colour, depth and appearance. Drying time - 1/2 to 2 hours.

CONTACT CEMENTAID FOR APPLICATION SERVICE.

WHERE RECOMMENDED:

Floors subject to oils, grease, lubricants, solvents, minerals, oils, mild acids, caustics, sugars, fruit juice, soft drinks etc., meatworks, dairy or food processing factories, ice-cream plants, sugar terminals, motor and electrical workshops, storage warehouses, etc.

CAUTION:

ROKITE (Clear) may discolour when exposed to sun. **ROKITE** is inflammable, and normal safeguards should be observed. Adequate ventilation must be provided. **ROKITE (Clear)** is fully compatible with Cementaid CALCURE CR. Use of other curing membranes will impair effectiveness, therefore use CALCURE CR, water or damp curing only.

ROKITE CLEAR: **ROKITE CLEAR** is the time-proven effective and durable surface treatment for protecting concrete floors in **Processing Plants, Motor & Electrical Workshops, Car Parks, Storerooms, Food Processing Plants, Sugar Terminals & Private Homes.**

ROKITE COLOUR: **ROKITE COLOUR** is the ideal hardwearing and cost-effective treatment for colouring and beautifying concrete floors. It is exceptionally resistant to staining by oil, grease and other spillages, which are easily wiped or hosed off.

SPECIFICATIONS

All floor surfaces or (specify areas) when cured, dry, clean and at least 14 days old shall be impregnated to resist corrosion and staining with **CEMENTAID ROKITE** (PR, AC, FR or EPS) at the rate of 1 litre per 4 square metres strictly in accordance with manufacturer's instructions for ensuring complete penetration. **NOTE:** It is strongly recommended that **DIAMITE** case-hardening surface densifier be applied, prior to the above, for increased effectiveness against wearing and dusting of the concrete due to traffic.

Where a non-slip surface is specially important use **CEMENTAID CALGRAINS** trowelled into surface of concrete during placing and finishing. For existing floors where extra traction is required, specify **ROKITE Non-Slip Grade**.

INDUSTRIAL FLOOR SPECIFICATIONS - GEL CONTROL AGENT - ANTI-CORROSION IMPREGNATIONS - OIL & SOLVENT PROOFING - WATERPROOFING - RAPID HARDENING RETARDING - SURFACE TOUGHENING - MORTAR AND DAMPCOURSE ADMIXTURES, ETC.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

[Contact Cementaid](#)

[Product Range](#)

[Home Page](#)

[Locations](#)

