

*you can **RELY** on*

CEMENTAID

The Way to Better Concrete

CEMENTAID INTERNATIONAL GROUP OF COMPANIES

Form Oils, Curing & Bonding Agents

CALBLOCK

Waterproofing of Block and Brick Retaining Walls

EFFECTS: Forms a dark brown, tough, flexible coating that is self-healing to some extent, adheres well to brick or blockwork, and is hydrophobic. After curing for 1 week, **CALBLOCK** will not re-emulsify when immersed in water. Not recommended in situations where a permanent hydrostatic pressure exists.

NOTE: **CALBLOCK** is a mixture of Polymeric Hydrophobic Bitumen linked with a synthetic Rubber Copolymer Latex, specifically designed for spraying onto vertical surfaces.

WHERE RECOMMENDED: For all Block and Brick walls requiring protection against ingress of ground or rain water. Also suitable for plain stone or concrete walls, in order to impart waterproof properties.

In order to fully damp-proof a block wall, the mortar should be mixed incorporating **CALBLOCK** at the ratio of 4 litres per 40kg bag of cement, in a 1 : 4 cement : sand mix. **CALBLOCK** can be mixed into the batch water, at the rate of 1 part **CALBLOCK** to 5 or 6 parts water.

APPLICATION: By spray, brush or roller. May be thinned up to 5% with water if required.

PACKING: 205 Litre drum, 20 Litre pail & 4 Litre bucket.

SPECIFICATIONS

All Block and Brick Walls shall be sprayed with three coats of **CALBLOCK** consecutively, allowing one hour between coats, applied to a nominal thickness of 250 microns per coat. The final coat shall be allowed to dry and react for at least 48 hours before backfilling commences.

INDUSTRIAL FLOOR SPECIFICATIONS - GEL CONTROL AGENT - ANTI-CORROSION
IMPREGNATIONS - OIL & SOLVENT PROOFING - WATERPROOFING - RAPID HARDENING
RETARDING - SURFACE TOUGHENING - MORTAR AND DAMPCOURSE ADMIXTURES, ETC.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

[Contact Cementaid](#)

[Product Range](#)

[Home Page](#)

[Locations](#)

SPEC-NET