


Dribond Colour Seal

A TOUGH FLEXIBLE SILICONISED WATER-RESISTANT SEALANT

PACKAGING




MIXING



APPLICATION



USES



SUBSTRATES

POROUS SURFACES
CERAMIC TILES
BRICK
BLOCK
CONCRETE
BATHS, BASINS
BUILDER BOARDS
EXPANSION CONTROL
JOINT IN LOW RISE
CONSTRUCTION

DESCRIPTION

Colour Seal is a tough, siliconised, flexible, durable water based sealant that is easily applied and pointed.

USES

An internal and external sealant for bathrooms and tiled areas and medium performance vertical control joints.

FEATURES

- Mould and UV light resistant.
- Can be applied to damp surfaces.
- Water based.

COVERAGE (Approximate)

5mm x 5mm joints – 12m/cartridge. 10mm x 10mm joints – 3.5m/cartridge.

COLOURS

White, Sandstone, Ivory, Light Grey, Mid Grey, Beige, Tan, Black.

PERFORMANCE DATA

Tensile Strength (ASTM 0412)	0.522 N/mm ²
Elongation (ASTM 0412)	205%

SPECIFICATION

The sealant shall be a water based acrylic and have a minimum performance of 205% Elongation and a Tensile Strength of 0.52 N/mm² such as Colour Seal manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's applications instructions.

JOINT PREPARATION

The surface to be sealed must be sound, clean, free of all contaminants and water.

APPLICATION

Cut the nozzle tip to the desired diameter and cut the seal on the cartridge.

Gun the sealant bead with a steady pressure. Push the sealant ahead of the nozzle to force the sealant into the joint and smooth the bead at the same time.

The surface can be smoothed with a wet knife, scraper or finger for up to 5 minutes after application. For best performance the sealant depth should be half the width.

CURING

Full cure occurs in 2-7 days depending on bead size, temperatures and humidity. Protect from moisture for 24 hours after application.

CLEANING

Remove uncured sealant with a wet cloth and cured mastic with a blade or knife.

LIMITATIONS:

DO NOT APPLY in immersed application or when temperatures are below 5°C or sections greater than 10mm x 10mm.

SHELF LIFE

2 years

**CONSTRUCTION
CHEMICALS**

- **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
- **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
- **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
- **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493
- **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
- **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
- **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING PH: (03) 552 2522 FAX: (03) 522 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."