


Gap Seal

A FLEXIBLE WHITE GAP FILLER

PACKAGING




MIXING



APPLICATION



USES



SUBSTRATES

CONCRETE
BRICK
BLOCK
CEMENT RENDER
BUILDING BOARDS
LAMINATED TOPS
CERAMIC TILES

DESCRIPTION:

Dribond Gap Seal is a water based acrylic gap sealant that provides a flexible, long lasting seal between surfaces where movement causes rigid gap fillers to crack and fall out. Dribond Gap Seal is suitable for interior and exterior applications and can be easily painted.

FEATURES:

- Interior and exterior use
- Flexible and paintable
- Water washable

USES:

- Along the tops of skirting boards, architraves and cornices
- Where doorframes/windowframes meet the wall
- Any gaps where some movement is expected

PERFORMANCE DATA

Elongation at break – 176% Maximum tensile strength – 0.68 Mpa Channel cracking - PASS (no cracks)

SPECIFICATIONS:

The sealant shall be a water based acrylic and have a minimum performance of 176% elongation and a tensile strength of 0.68Mpa such as Dribond Gap Seal manufactured by Construction Chemicals and shall be applied in accordance with manufacturers application instructions.

JOINT PREPARATION

The surface to be sealed must be sound, clean and free of any contaminants and surface water.

APPLICATION

Cut the nozzle tip to the desired diameter and cut the seal on the cartridge. Gun the sealant bead with a steady pressure. Push the sealant ahead of the nozzle to force the sealant into the joint and smooth the bead at the same time. The surface can be smoothed with a wet knife, scraper or finger for up to 5 minutes after application.

CURING: Full cure occurs in 2-7 days depending on bead size, temperatures and humidity. Protect from moisture for 48 hours after application.

CLEANING: Remove uncured Gap Seal with a wet cloth or sponge and cured Gap Seal with a blade or knife.

LIMITATIONS:

Do not apply in immersed application or when temperatures are below 5°C or sections greater than 10mm (depth) x 20mm (width). Allow longer curing times for damp conditions. Do not use for tongue and groove flooring. Not suitable for bathrooms and kitchens use Dribond Colour Seal.

STORAGE: Store product in dry conditions.

**CONSTRUCTION
CHEMICALS**

- **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
- **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
- **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
- **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493
- **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
- **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
- **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING PH: (03) 552 2522 FAX: (03) 522 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."