

# Kemcote Gloss

**A CLEAR GLOSS “WET LOOK” COATING FOR POROUS SURFACES AND SLATE**


**PACKAGING**




**MIXING**



**APPLICATION**



**USES**



**SUBSTRATES**

**WALLS –**  
CONCRETE, BRICK  
BLOCK  
CEMENT RENDER  
STONE  
**FLOORS –**  
SLATE & CONCRETE

**DESCRIPTION**

A clear gloss “wet look” non-yellowing, hard-wearing, solvent based coating that highlights colour, seals and protects porous surfaces and slate.

**USES**

Seals and protects, slate, unglazed tiles, stone, concrete, brick, block and concrete surfaces.

**FEATURES**

- Long lasting – tests have shown years of dependable protection.
- Seals surface from moisture and protects surface from atmospheric chemical attack.
- Will not darken or yellow with age.
- Reduced weather staining – vertical surfaces tend to be self cleaning.
- May be recoated at any time.

**COVERAGE** (Approximate)

8-10 m<sup>2</sup>/litre/coat.

**PERFORMANCE DATA**

**Surface Water Absorption** BS1881 Parts Section 6

Short term (1 hour) 0.0095 (ml/m<sup>2</sup>/sec)

Long term (24 hours) 0.0103 (ml/m<sup>2</sup>/sec)

Reduces moisture absorption by 85%

**Chemical Resistance**

Moderate resistance to acids and alkali

**Weathering**

2000 hours QUV

Slight gloss reduction

**SPECIFICATION**

The sealer shall be a solvent acrylic sealer and reduce water absorption by 85% and have good weather resistance such as Kemcote Gloss manufactured by Construction Chemicals and shall be applied in accordance with the application instructions.

**SURFACE PREPARATION**

Surface to be coated must be firm, clean, dry and free of oil, grease, efflorescence, contaminants and other coatings. Do not apply over paint, loose or crumbly surfaces or to very dense impervious surfaces such as marble tiles or polished stone. New concrete should have cured for 28 days and allow damp substrates up to 3 days to dry thoroughly depending on temperature. New floors are cleaned by scrubbing with warm water mixed with a mild household detergent, washed with clean water and allowed to dry thoroughly. If the substrate is not completely dry or is in prolonged damp situations the coating will discolour.

**To check the suitability of a sealer apply a test area before commencing.**

## APPLICATION

Apply in temperatures above 5°C. Apply with fine hair brush, roller or low pressure spray (35-100). Apply two coats, the first to saturate the surface. Avoid applying excessive thicknesses or in puddles. Allow 2-3 hours between coats. Apply the second coat evenly without leaving streaks or brush marks. Allow surface to dry before putting into use. When recoating after areas have been in use for some time, scrub area with detergent to remove dirt and grease and wash with clean water and let dry for 2-3 days before recoating.

## STORAGE

Keep in a cool dry place away from open fires, heater and stoves etc.

## PRECAUTIONS

Kemcote Gloss will be marked or scratched in highly abrasive traffic areas. Protect the surface from scratching by using felt pads on the base of furniture. Do not use in situations where rising damp is present.

## SOLVENT

Xylol or similar.

## SAFETY INSTRUCTIONS

Contains flammable solvents in the liquid state. Do not smoke during application or apply in the presence of naked flames, electrical equipment or sparks. Ensure adequate ventilation during application and drying period. Avoid contact with skin or eyes, breathing vapour or mist spray. Keep out of children's reach.

## FIRST AID

If swallowed do not induce vomiting. Give a glass of water and contact a doctor or Poisons Information Centre.

## SHELF LIFE

2 years



● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052  
● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892  
● **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748  
● **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493  
● **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534  
● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236  
● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING  
PH: (03) 552 2522 FAX: (03) 522 2526