



**WATER REPELLANT SEALER FOR POROUS MASONRY SURFACES. DOES NOT CHANGE APPEARANCE**
**PACKAGING**

**MIXING**

**APPLICATION**

**USES**

**SUBSTRATES**
**WALLS  
CONCRETE, BRICK  
BLOCK  
FLOOR  
STONE, POROUS  
UNGLAZED TILES**
**DESCRIPTION**

**Prime Seal** is a water based penetrating sealer for use on porous masonry surfaces, porous tiles, grout, brick, concrete and natural porous stones.

**USES**

Water repellent sealer for grout, concrete, natural porous stones and applying to porous tiles before grouting or applying **Terra Guard** wax system.

**FEATURES**

- Does not change appearance
- Suitable for internal and external application
- Simple to apply
- Suitable for pre-sealing terracotta
- Reduces staining
- Water based

**COVERAGE**

1 L covers approx. 6-10m<sup>2</sup>. 2-3 coats required depending on porosity.

**SPECIFICATION**

The sealer shall be a water based, penetrating sealer such as Prime Seal, manufactured by Construction Chemicals and shall be applied according to the manufacturer's application instructions.

**SURFACE PREPARATION**

Make sure surface is clean, dry and has no previous sealer. **Always apply to a test area before commencing to ensure suitability.**

**APPLICATION**

**Prime Seal** can be applied easily with a brush, spray or roller. Apply one coat taking care to avoid puddling. **Do not allow the sealer to dry on the surface**, any material not absorbed after 5 minutes should be wiped off with paper towels or clean rags. For high porosity surfaces a second or even third application may be necessary immediately after the previous coat. For best results apply until surface will no longer absorb the material, always ensuring excess is wiped off. Allow 24 hours to cure. Stain reduction should be tested with substances common to the area. Avoid contact with glass and metals.

**SAFETY**

**Prime Seal** is poisonous if swallowed, avoid contact with skin and eyes. Keep out of the reach of children. Wear approved gloves and eye protection.

**FIRST AID**

If swallowed contact a doctor. Do not induce vomiting. If in eyes flood with water for about 15 minutes and seek medical advice.

**SHELF LIFE**

2 Years.

**CONSTRUCTION  
CHEMICALS**

● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052  
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892  
 ● **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748  
 ● **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493  
 ● **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534  
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236  
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING  
 PH: (03) 552 2522 FAX: (03) 522 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."