

PREMIXED FLEXIBLE ACRYLIC ADHESIVE

PACKAGING



MIXING




APPLICATION



WALLS—6mm Notch

USES



SUBSTRATES

GYPSUM BUILDING
BOARD
CEMENT SHEET
PLYWOOD
CEMENT RENDER
BRICK, BLOCK
CONCRETE

DESCRIPTION

Surefix is a white premixed thin bed acrylic based ceramic tile adhesive.

USES

Fixing ceramic and mosaic tiles to clean and firm walls of plaster, gyprock, cement sheeting, cement render, bathrooms, laundries shower alcoves, external patios.

Do not use the adhesive between two impervious surfaces as the adhesive will not set.

COVERAGE (Approximate)

1 m²/litre (1.5kg)

PERFORMANCE DATA

Exceeds the performance requirements of AS2358 and BS5385

Shear Bond Strength (2.49Mpa)

SPECIFICATION

The ceramic tile adhesive shall be a premixed flexible acrylic adhesive that exceeds the requirements of AS2358 and BS5385 and has a minimum shear bond strength of 2.49Mpa such as Surefix manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

SURFACE PREPARATION

Surfaces must be free from dirt, dust, grease, and other contaminants. Building boards must be firmly fixed at 450 mm centres to restrain movement with rough side out where possible. Remove paint and prime highly absorbent surfaces (i.e. cement sheeting) with Primer and Grout Additive and allow to dry before application of adhesive.

APPLICATION

Apply the Surefix with a 6mm x 6mm notched trowel. Spread only 1 m² at a time as the adhesive dries rapidly.

Immediately press dry tiles into the ribs of adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Remove any excess adhesive from the surface of the tile before it dries using a damp cloth. The adhesive bed should not be less than 1.6mm or greater than 3.5mm thick.

GROUTING

Allow adhesive to set for 24 hours before grouting with Kemgrout Flexible.

SHELF LIFE 2 years

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493
 ● **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECABI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 PH: (03) 552 2522 FAX: (03) 522 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."