

WHITE PREMIXED NON-SLIP FLEXIBLE WALL ADHESIVE

PACKAGING



MIXING




APPLICATION



WALLS-6mm Notch

USES



SUBSTRATES

GYPSUM BUILDING BOARD
CEMENT SHEET
CEMENT RENDER
BRICK, BLOCK
CONCRETE

DESCRIPTION

Tilemastic is an easily spread, white premixed, water resistant, flexible wall tile adhesive with excellent non-slip properties and bond strength. Exceeds AS2358-1990.

USES

Fixing all types of ceramic wall tiles to clean and firm walls of plaster, gyprock, cement sheeting and cement render in kitchens, bathrooms, laundries and shower alcoves. **Tilemastic** is especially designed for large tiles (300mm sq./1.5 kg) and tiling from the top eliminating the need for straight edges.

PERFORMANCE DATA

Exceeds the performance requirements of AS2358 and BS5385.

Shear Bond strength 3.44 MPA.

SPECIFICATION

The ceramic tile adhesive shall be a premixed flexible acrylic adhesive that exceeds the requirements of AS2358 and BS5385 and has a minimum shear bond strength of 3.44 MPA such as **Tilemastic** manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

SURFACE PREPARATION

Surfaces must be free from dirt, dust, grease and other contaminants. Building boards must be firmly fixed at 450mm centres to restrain movement with rough side out where possible. Remove any paint and prime highly absorbent surfaces (ie. cement sheeting) with **Primer & Grout Additive** and allow to dry before application of adhesive.

APPLICATION

Apply the **Tilemastic** with a 6mm x 6mm notched trowel. Spread only 1m² at a time as the adhesive dries rapidly. Immediately press dry tiles into the ribs of the adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Remove any excess adhesive from the surface of the tile before it dries using a damp cloth. The adhesive bed should be not less than 1.6mm or greater than 3.5mm thick. **Do not use between two non porous surfaces as the adhesive will not set. Not suitable for immersed applications, Construction Chemicals provide other systems.**

COVERAGE

2Kg per m² (approximately)

GROUTING

Allow 24 hours before commencing, longer in cold damp conditions or dense tiles.

Use **Primer & Grout Additive** or **Flexible Grout Additive** with **Kemgrout**.

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 1 / 10 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 61 DOWD ST WELSHPOOL 6106 PH: (08) 9358 6493 FAX: (08) 9358 6493
 ● **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 PH: (03) 552 2522 FAX: (03) 522 2526

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."