

Paraterm Bar™

ALUMINIUM TERMINATION BAR

Key Benefits Summary

- Easy installation
- Predrilled fixing holes

PRODUCT INFORMATION

BASIC USE

Paraterm is a high performance roofing and waterproofing product for systems which require or prefer accessories of the highest quality good looks and long life. When fastened through the pre-cut holes, Paraterm provides tight, straight and extremely long lived terminations, caulk troughs and drip edges. Paraterm can be inverted to protect the edges of waterproofing products which do not require a caulk edge.

MATERIALS

Paraterm is composed of an aluminium alloy specifically formulated to exhibit terrific holding power. 115 mil finish is 13% heavier than most termination bars in common use. This high strength assures bowless installations making Paraterm excellent for the attachment of both single ply and modified sheet materials.

PACKAGING

3.05 metre lengths.

LIMITATIONS

Allow for expansion and contraction when used above grade. Make certain fasteners are centred in holes.

USAGE GUIDELINES

INSTALLATION

Preparatory Work:

Substrate should be reasonably straight and sound enough to provide a permanent attachment. Position fasteners to allow a small amount of expansion and contraction movement.

TECHNICAL INFORMATION

TECHNICAL DATA

Length - One section	3.05m
Yield	12%
Hardness Burnell #73	510 KG (on a 10mm Ball)

TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specifications of products. For more detailed information or service and advice call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

We warrant our products to be free of defects and manufactured to meet published physical properties when tested according to applicable specifications and TREMCO standards.

Under this warranty we will provide at no charge, product to replace any product proven to be defective when applied in accordance with our written instructions and in applications recommended by TREMCO as being suitable for this product.

All claims concerning product defects must be made within 12 months of shipment. Absence of such claims in writing during this period will contribute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.